


TEMPERATURE-TABLE for PTCR

Higher quality products and lower costs through improved, reliable firing control

Type PTCR - LTH	:	4322 020 07061	Ring Colour	:	Red
Ferro No.	:	1007154	Dimensions	:	± 20 x 10 x 7,0 mm
Temperature Range °C	:	970 - 1250°C			

Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature	Ring diameter	Ring temperature
mm	°C	mm	°C	mm	°C	mm	°C	mm	°C	mm	°C
				19,18	1201 °	19,68	1118 °				
				19,19	1200 °	19,69	1115 °				
				19,20	1199 °	19,70	1112 °				
				19,21	1198 °	19,71	1110 °				
				19,22	1196 °	19,72	1107 °				
				19,23	1195 °	19,73	1104 °				
				19,24	1194 °	19,74	1101 °				
				19,25	1193 °	19,75	1098 °				
				19,26	1192 °	19,76	1095 °				
				19,27	1190 °	19,77	1092 °				
				19,28	1189 °	19,78	1089 °				
				19,29	1188 °	19,79	1085 °				
				19,30	1186 °	19,80	1082 °				
				19,31	1185 °	19,81	1079 °				
		18,82	1251 °	19,32	1184 °	19,82	1075 °				
		18,83	1249 °	19,33	1183 °	19,83	1072 °				
		18,84	1247 °	19,34	1181 °	19,84	1068 °				
		18,85	1246 °	19,35	1180 °	19,85	1064 °				
		18,86	1244 °	19,36	1178 °	19,86	1061 °				
		18,87	1242 °	19,37	1177 °	19,87	1057 °				
		18,88	1241 °	19,38	1176 °	19,88	1053 °				
		18,89	1239 °	19,39	1174 °	19,89	1049 °				
		18,90	1238 °	19,40	1173 °	19,90	1045 °				
		18,91	1236 °	19,41	1171 °	19,91	1041 °				
		18,92	1235 °	19,42	1170 °	19,92	1037 °				
		18,93	1233 °	19,43	1168 °	19,93	1032 °				
		18,94	1232 °	19,44	1167 °	19,94	1028 °				
		18,95	1230 °	19,45	1165 °	19,95	1023 °				
		18,96	1229 °	19,46	1163 °	19,96	1019 °				
		18,97	1227 °	19,47	1162 °	19,97	1014 °				
		18,98	1226 °	19,48	1160 °	19,98	1009 °				
		18,99	1225 °	19,49	1158 °	19,99	1005 °				
		19,00	1223 °	19,50	1157 °	20,00	1000 °				
		19,01	1222 °	19,51	1155 °	20,01	995 °				
		19,02	1221 °	19,52	1153 °	20,02	989 °				
		19,03	1220 °	19,53	1151 °	20,03	984 °				
		19,04	1218 °	19,54	1149 °	20,04	979 °				
		19,05	1217 °	19,55	1147 °	20,05	973 °				
		19,06	1216 °	19,56	1145 °	20,06	968 °				
		19,07	1214 °	19,57	1143 °						
		19,08	1213 °	19,58	1141 °						
		19,09	1212 °	19,59	1139 °						
		19,10	1211 °	19,60	1137 °						
		19,11	1210 °	19,61	1135 °						
		19,12	1208 °	19,62	1132 °						
		19,13	1207 °	19,63	1130 °						
		19,14	1206 °	19,64	1128 °						
		19,15	1205 °	19,65	1125 °						
		19,16	1204 °	19,66	1123 °						
		19,17	1202 °	19,67	1120 °						

Powder Batch #	:	140	Batch approved	
Date	:	21/05/2013	Quality Inspection :	

For inquiries :

Customer Service Desk

Phone : +49 69 27116 432

Fax : +49 69 27116 243

