



Performance Pigments &amp; Colors

FERRO (FRANCE) SARL  
43, RUE JEANNE D'ARC  
52115 SAINT-DIZIER CEDEX  
FRANCE

TEMPERATURE-TABLE for PTCR											
Higher quality products and lower costs through improved, reliable firing control											
Type PTCR - LTH						Ring Colour : Red					
Ferro No. : 1400604						Dimensions : ± 20 x 10 x 7,0 mm					
Temperature Range °C : 970 - 1250°C	Ring diameter mm	Ring temperature °C	Ring diameter mm	Ring temperature °C	Ring diameter mm	Ring diameter mm	Ring temperature °C	Ring diameter mm	Ring temperature °C	Ring diameter mm	Ring temperature °C
				19,28 19,29 19,30 19,31 19,32	1202 ° 1200 ° 1199 ° 1198 ° 1196 °	19,78 19,79 19,80 19,81 19,82	1094 ° 1091 ° 1087 ° 1083 ° 1079 °				
				19,33 19,34 19,35 19,36 19,37	1195 ° 1193 ° 1192 ° 1191 ° 1189 °	19,83 19,84 19,85 19,86 19,87	1075 ° 1071 ° 1067 ° 1062 ° 1058 °				
				19,38 19,39 19,40 19,41 19,42	1188 ° 1186 ° 1185 ° 1183 ° 1181 °	19,88 19,89 19,90 19,91 19,92	1054 ° 1049 ° 1044 ° 1039 ° 1034 °				
				19,43 19,44 19,45 19,46 18,97	1180 ° 1178 ° 1177 ° 1175 ° 1250 °	19,93 19,94 19,95 19,96 19,47	1029 ° 1024 ° 1019 ° 1014 ° 1173 °				
				18,98 18,99 19,00 19,01 19,02	1248 ° 1246 ° 1245 ° 1243 ° 1241 °	19,48 19,49 19,50 19,51 19,52	1002 ° 997 ° 991 ° 985 ° 1164 °	20,00 20,01 20,02	979 °		
				19,03 19,04 19,05 19,06 19,07	1239 ° 1237 ° 1236 ° 1234 ° 1232 °	19,53 19,54 19,55 19,56 19,57	1162 ° 1160 ° 1158 ° 1156 ° 1154 °	20,03 20,04	972 ° 966 °		
				19,08 19,09 19,10 19,11 19,12	1231 ° 1229 ° 1227 ° 1226 ° 1224 °	19,58 19,59 19,60 19,61 19,62	1152 ° 1149 ° 1147 ° 1145 ° 1142 °				
				19,13 19,14 19,15 19,16 19,17	1223 ° 1221 ° 1220 ° 1219 ° 1217 °	19,63 19,64 19,65 19,66 19,67	1140 ° 1137 ° 1135 ° 1132 ° 1129 °				
				19,18 19,19 19,20 19,21 19,22	1216 ° 1214 ° 1213 ° 1211 ° 1210 °	19,68 19,69 19,70 19,71 19,72	1126 ° 1124 ° 1121 ° 1118 ° 1115 °				
				19,23 19,24 19,25 19,26 19,27	1209 ° 1207 ° 1206 ° 1205 ° 1203 °	19,73 19,74 19,75 19,76 19,77	1111 ° 1108 ° 1105 ° 1101 ° 1098 °				
Powder Batch # : 150	Batch approved			Date : 05/01/2017	Quality Inspection :						

For inquiries :

Customer Service Desk

Phone : +49 69 27116 432

Fax : +49 69 27116 243

sheet 367-150 - 010

