


TEMPERATURE-TABLE for PTCR
Higher quality products and lower costs through improved, reliable firing control

| Type PTCR - LTH | | | | | | Ring Colour | Red | | | | | |
|-------------------------------------|------------------|---------------|------------------|---------------|------------------|---------------|--------------------|---------------|------------------|---------------|------------------|---------------|
| Ferro No. : 1400604 | | | | | | Dimensions | ± 20 x 10 x 7,0 mm | | | | | |
| Temperature Range °C : 970 - 1250°C | | | | | | | | | | | | |
| Ring diameter | Ring temperature | Ring diameter | Ring temperature | Ring diameter | Ring temperature | Ring diameter | Ring temperature | Ring diameter | Ring temperature | Ring diameter | Ring temperature | Ring diameter |
| mm | °C | mm | °C | mm | °C | mm | °C | mm | °C | mm | °C | mm |
| | | | | 19,18 | 1212 ° | 19,68 | 1127 ° | | | | | |
| | | | | 19,19 | 1210 ° | 19,69 | 1124 ° | | | | | |
| | | | | 19,20 | 1209 ° | 19,70 | 1122 ° | | | | | |
| | | | | 19,21 | 1207 ° | 19,71 | 1119 ° | | | | | |
| | | | | 19,22 | 1206 ° | 19,72 | 1116 ° | | | | | |
| | | | | 19,23 | 1205 ° | 19,73 | 1113 ° | | | | | |
| | | | | 19,24 | 1203 ° | 19,74 | 1111 ° | | | | | |
| | | | | 19,25 | 1202 ° | 19,75 | 1108 ° | | | | | |
| | | | | 19,26 | 1200 ° | 19,76 | 1105 ° | | | | | |
| | | | | 19,27 | 1199 ° | 19,77 | 1102 ° | | | | | |
| | | | | 19,28 | 1198 ° | 19,78 | 1099 ° | | | | | |
| | | | | 19,29 | 1196 ° | 19,79 | 1096 ° | | | | | |
| | | | | 19,30 | 1195 ° | 19,80 | 1092 ° | | | | | |
| | | | | 19,31 | 1193 ° | 19,81 | 1089 ° | | | | | |
| | | | | 19,32 | 1192 ° | 19,82 | 1086 ° | | | | | |
| | | | | 19,33 | 1190 ° | 19,83 | 1082 ° | | | | | |
| | | | | 19,34 | 1189 ° | 19,84 | 1079 ° | | | | | |
| | | | | 19,35 | 1188 ° | 19,85 | 1075 ° | | | | | |
| | | | | 19,36 | 1186 ° | 19,86 | 1071 ° | | | | | |
| | | | | 19,37 | 1185 ° | 19,87 | 1068 ° | | | | | |
| | | | | 19,38 | 1183 ° | 19,88 | 1064 ° | | | | | |
| | | | | 19,39 | 1182 ° | 19,89 | 1060 ° | | | | | |
| | | | | 19,40 | 1180 ° | 19,90 | 1056 ° | | | | | |
| | | | | 19,41 | 1179 ° | 19,91 | 1052 ° | | | | | |
| | | | | 19,42 | 1177 ° | 19,92 | 1047 ° | | | | | |
| | | | 18,95 | 1251 ° | 19,43 | 1176 ° | 19,93 | 1043 ° | | | | |
| | | | 18,96 | 1249 ° | 19,44 | 1174 ° | 19,94 | 1039 ° | | | | |
| | | | 18,97 | 1247 ° | 19,45 | 1172 ° | 19,95 | 1034 ° | | | | |
| | | | 18,98 | 1245 ° | 19,46 | 1171 ° | 19,96 | 1030 ° | | | | |
| | | | 18,99 | 1243 ° | 19,47 | 1169 ° | 19,97 | 1025 ° | | | | |
| | | | 19,00 | 1241 ° | 19,48 | 1168 ° | 19,98 | 1020 ° | | | | |
| | | | 19,01 | 1240 ° | 19,49 | 1166 ° | 19,99 | 1015 ° | | | | |
| | | | 19,02 | 1238 ° | 19,50 | 1164 ° | 20,00 | 1011 ° | | | | |
| | | | 19,03 | 1236 ° | 19,51 | 1162 ° | 20,01 | 1005 ° | | | | |
| | | | 19,04 | 1234 ° | 19,52 | 1161 ° | 20,02 | 1000 ° | | | | |
| | | | 19,05 | 1232 ° | 19,53 | 1159 ° | 20,03 | 995 ° | | | | |
| | | | 19,06 | 1231 ° | 19,54 | 1157 ° | 20,04 | 990 ° | | | | |
| | | | 19,07 | 1229 ° | 19,55 | 1155 ° | 20,05 | 984 ° | | | | |
| | | | 19,08 | 1227 ° | 19,56 | 1153 ° | 20,06 | 979 ° | | | | |
| | | | 19,09 | 1226 ° | 19,57 | 1151 ° | 20,07 | 973 ° | | | | |
| | | | 19,10 | 1224 ° | 19,58 | 1149 ° | 20,08 | 967 ° | | | | |
| | | | 19,11 | 1222 ° | 19,59 | 1147 ° | | | | | | |
| | | | 19,12 | 1221 ° | 19,60 | 1145 ° | | | | | | |
| | | | 19,13 | 1219 ° | 19,61 | 1143 ° | | | | | | |
| | | | 19,14 | 1218 ° | 19,62 | 1141 ° | | | | | | |
| | | | 19,15 | 1216 ° | | | | | | | | |
| | | | 19,16 | 1215 ° | | | | | | | | |
| | | | 19,17 | 1213 ° | | | | | | | | |

| | | |
|------------------|------------|-----------------------------------------------------------------------------------------------------------|
| Powder Batch # : | 170 | Batch approved |
| Date : | 24/11/2021 | Quality Inspection :  |

For inquiries :

Customer Service Desk

Phone : +49 69 27116 432

Fax : +49 69 27116 243